



PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 9/12/2025

SECTION 1: IDENTIFICATION

1.1 Product Identifier

Product Form: Mixture

Product Name: Petroleum Pavement Sealer Base

CAS-No.: 64741-62-4

Synonyms: Clarified oils (petroleum), catalytic cracked

1.2. Intended Use of the Product

Use of the Substance/Mixture: Pavement Maintenance

1.3 Name, Address, and Telephone of the Responsible Party

Company:

Lone Star Specialty Products, LLC

6412 U.S. Highway 259 South

Lone Star, TX 75668 USA

www.lonestarspecialties.net

1.4 Emergency Phone Number

Emergency Number: 800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Asp. 1	H304
Acute Tox. 4 (Inhale)	H332
Muta. 2	H341
Carc. 1A	H350
Repr. 1B	H361
STOT RE 2	H373
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Full text of hazard classes and H-statements: See section 16

2.2 Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US):



Signal Word (GHS-US): Danger

Hazard Statements (GHS-US): H304 – May be fatal if swallowed and enters airways.
H332 – Harmful if inhaled.

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H341 – Suspected of causing genetic defects.

H350 – May cause cancer.

H361 – Suspected of damaging fertility or the unborn child.

H373 – May cause damage to organs through prolonged or repeated exposure.

H400 – Very toxic to aquatic life.

H410 – Very toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US):

P203 – Obtain, read and follow all safety instructions before use.

P260 – Do not breathe dust/fume/gas/mist/vapors/spray.

P261 – Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 – Use only outdoors or in well-ventilated area.

P273 – Avoid release to the environment.

P280 – Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301 + P316 – IF SWALLOWED: Get emergency medical help immediately.

P304 + P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P317 – Get emergency medical help.

P318 – If exposed or concerned, get medical advice.

P319 – Get medical help if you feel unwell.

P331 – Do NOT induce vomiting.

P391 – Collect spillage.

P405 – Store locked up.

P501 – Dispose of contents/container properly.

2.3 Other Hazards

Individuals with preexisting skin disorders or central nervous functional illnesses may be at increased risk from overexposure. Exposure to vapor may aggravate preexisting lung condition.

2.4 Unknown Acute Toxicity (GHS-US)

No data available.

Emergency Overview: A black liquid with an aromatic odor. Combustible Liquid. This substance has been associated with acute and chronic health effects, including cancer. Material will burn if ignited. Harmful if inhaled. Causes skin irritation. May cause eye and respiratory tract irritation.

Primary Routes of Exposure: Eyes, dermal, inhalation, ingestion.

Potential Acute Health Effects: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects: CARCINOGENIC EFFECTS: Classified 1 (Proven for human.) by IARC, 1 (Clear evidence; known carcinogen) by NTP.

MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast.

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No 1272/2008

GHS08 health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

Medical Conditions Aggravated by Exposure: Persons with preexisting skin disorders or central nervous functional illnesses may be at increased risk from overexposure. Exposure to vapor may aggravate preexisting lung condition.

Signs and symptom Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation. Defatting of the skin.

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS

3.1 Substance

Name: Decant Oil Distillation Residue

CAS-No.: 64741-62-4

Name	Synonyms	Product Identifier	%	GHS US classification
Decant oil distillation residue	Petroleum Pavement Sealer Base/Clarified oils (petroleum), catalytic cracked	(CAS-No.) 64741-62-4	100	Asp. 1, H304 Acute Tox. 4 (Inhale), H332 Muta. 2, H341 Carc. 1A, H350 Repr. 1B, H361 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: See section 16

3.2 Mixture

Not applicable

SECTION 4: FIRST AID MEASURES

4.1 Description of First-Aid Measures

Skin Contact: For contact with hot molten material, immerse or flush skin with cold water for at least 15 minutes. Call a physician. Cold material over a burn should not be removed except by a physician. Remove cold material (not associated with a burn) with waterless hand cleaner and then wash with soap and water.

Eye Contact: Rinse eyes immediately with large amounts of water for at least 15 minutes, occasionally lifting the eyelids. Seek medical attention/advise if irritation persists.

Inhalation: Remove from exposure area to fresh air immediately. If breathing has stopped, give artificial respiration. Keep affected person warm and at rest. Give oxygen if respiration is shallow. Seek medical attention/advise if irritation persists.

Ingestion: Don not induce vomiting. Give oxygen if respiration is shallow. Seek medical attention/advise if irritation persists. Do not give anything by mouth to an unconscious person.

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Fedral Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Thermal Exposure: Contact with molten pitch causes serious burns. For contact with molten product, do not remove contaminated clothing. Flush skin immediately with large amounts of cold water. If possible, submerge area in cold water. Pack affected area with ice and GET MEDICAL ATTENTION immediately.

Note to Physician: No specific antidote known. Treatment should be based on the judgment of the physician in response to the reactions of the patient.
Recommended practice is to not attempt to remove hot material associated with a burn. Allow the solidified material to remain in place until cooled so it can naturally fall off. Natural separation will occur in 48-72 hours.

SECTION 5: FIRE FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media: dry chemical, CO₂, foam, and water fog.

Unsuitable Extinguishing Media: water may be ineffective.

5.2 Special Hazards Arising from the Substance or Mixture

Fire Hazard: Products are classified as flammable/combustible based on flash point as defined in the Health Canada control products. Regulations U.S. Occupational Health and Safety Administration Hazard Communication Standard and transportation regulations. See Sections 1, 2, & 5 for flammable/combustible classification information. Flammable/combustible materials may ignite and burn if exposed to a flame or other sources of ignition.

Explosion Hazard: Do not store near strong oxidants or open flame. Smoke from fire may be hazardous.

Reactivity: OILS: CLARIFIED react with acids to liberate heat. Heat is also generated by interaction with caustic solutions. Strong oxidizing acids may cause a vigorous reaction that is sufficiently exothermic to ignite the reaction products. Flammable hydrogen is generated by mixing with alkali metals and hydrides.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

General Measures:

6.1.1 For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2 For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2 Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3 Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: **SMALL DRY SPILL:** With clean shovel, place material into clean, dry container and cover loosely; move containers from spill area. **SMALL SPILL:** Pick up with sand or other non-

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Fedral Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

combustible absorbent material and place into containers for later disposal. **LARGE SPILL:** Dike far ahead of liquid spill for later disposal. Cover powder spill with plastic sheet or tarp to minimize spreading.

Prevent entry into waterways, sewers, basements or confined areas.

Wear protective equipment during cleanup. Remove all ignition sources. Ventilate area of spill or leak.

Isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids. Increase the immediate precautionary measure distance, in the downwind direction, as necessary.

Evacuation Procedures: Isolate the release area and deny entry to unnecessary and unprotected personnel.

6.4 Reference to Other Sections

See section 8 for exposure controls and personal protection and section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for Safe Handling

Additional Hazards When Processed: Protect containers from physical damage, sparks and flame.

Precautions for Safe Handling: Wear appropriate protective equipment when performing maintenance on contaminated equipment. Avoid prolonged or repeated contact with skin or breathing of vapors. Do not smoke or eat in areas where the material is handled. Wash hands thoroughly before eating, drinking, or smoking. A complete soap and water shower should be taken at the end of each workday. Contaminated clothing should not be re-worn until cleaned. Launder contaminated clothing separately from other laundry before reuse.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2 Conditions for Safe Storage, Including Any Incompatibles

Technical Measures: Comply with applicable regulations

Storage Conditions: Outside or detached storage is preferable. Maintain cool, dry, ventilated conditions for storage. Containers should be periodically inspected.

7.3 Specific End Uses(s)

Pavement Sealer

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Control Parameters

Clarified oils (Petroleum), catalytic cracked (64741-62-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Physical State:	Liquid
Appearance, State & Odor:	Yellow-brown liquid
Odor:	Strong tarry odor
Odor Threshold:	No data available
pH:	Neutral
Evaporation Rate:	No data available
Flash Point (open cup):	205°C (401°F)
Auto-Ignition Temperature:	>260°C (500°F)
Decomposition Temperature:	No data available
Flammability:	LFL = 0.6%; UFL = 7%
Relative Density:	1 g/cm ³
Viscosity:	No data available
Vapor Pressure:	No data available
Vapor Density:	>4
Boiling Point:	500-1150°F
Melting Point:	No data available
Solubility in Water:	Insoluble in water
Specific Gravity:	No data available
Softening Point:	45 -50, ring and ball method
Bulk Density:	No data available
Octanol/Water Partition Coefficient:	No data available

SECTION 10: STABILITY AND REACTIVITY

- | | |
|---|--|
| 10.1 Chemical Stability: | Stable under normal temperature conditions and recommended use. |
| 10.2 Conditions to Avoid: | Heat, flames and sparks. Ignition sources. Contact with incompatible materials. Avoid static discharge and generation of dust. Do not store near strong oxidants. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition. |
| 10.3 Incompatible Materials: | Strong oxidizing agents. Acids. Alkalis. |
| 10.4 Hazardous Decomposition Products: | Under fire conditions – may form toxic materials; carbon monoxide and dioxide, oxides of sulfur, H ₂ S and other decomposition products, in the case of incomplete combustion. |

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Acute Toxicity (Oral): may cause lung damage

Acute Toxicity (Dermal): not classified

Acute Toxicity (Inhalation): harmful if inhaled

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decant Oil Distillation Residue (64741-62-4)	
LD50 Oral Rat	490 mg/kg
LD50 Dermal Rabbit	>2 g/kg
LC50 Inhalation Mouse	>0.025 mg/l, 960 minutes

Decant Oil Distillation Residue (64741-62-4)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen List

Reproductive Toxicity: Suspected of damaging fertility or the unborn child. Can cause adverse reproductive effects – such as birth defects, miscarriages, or infertility.

Organ Toxicity: May cause damage to the following organs through prolonged or repeated exposure: Blood. Liver. Kidneys.

Skin Corrosion/Irritation: Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious Eye Damage/Irritation: May cause eye irritation.

Carcinogenicity: Suspected of causing cancer.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: Irritation of nose and throat.

Symptoms/Injuries After Skin Contact: Skin irritation, drying, cracking. Defatting of the skin. Rash.

Symptoms/Injuries After Eye Contact: Irritation of eyes and mucous membranes. Corneal damage.

Chronic Symptoms: Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication. Repeated exposure to naphthalene may cause cataracts, allergic skin rashes, destruction of red blood cells, and anemia, jaundice, kidney and liver damage. Danger of serious damage to health by prolonged exposure. Prolonged or repeated overexposure may cause central nervous system, kidney, liver, and lung damage.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Ecotoxicity: Very toxic to aquatic life with long lasting effects.

Hydrogen Sulfide (7783-06-4)	
LC50 Fish	0.007mg/L, 96 hours

Naphthalene (91-20-3)	
LC50 Fish	0.95 – 1.62 mg/l, 96 hours

Residues (Petroleum), light vacuum (68512-62-9)	
LC50 Fish	48 mg/L, 48 hours

12.2 Persistence and Degradability

No information available.

12.3 Mobility in Soil

No information available.

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4 Other Adverse Effects

No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal Recommendations: Dispose in accordance with all applicable regulations. This material and its container must be disposed of as hazardous waste. Dispose of this material and its container to hazardous or special waste collection points. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used containers.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.


14.1 In Accordance with DOT

Proper Shipping Name: Elevated temperature liquid, n.o.s.
Hazard Class: 9
Identification Number: UN 3257
Packing Group: III
ERG Number: 171



14.2 In Accordance with IMDG

Proper Shipping Name: Elevated temperature liquid, n.o.s.
Hazard Class: 9
Identification Number: UN3257
Packing Group: III
Label Codes: 9
EmS-No. (Fire): F-A
EmS-No. (Spillage): S-A



14.3 In Accordance with IATA

Proper Shipping Name: Elevated temperature liquid, n.o.s.
Hazard Class: 9
Packing Group: 3
Identification Number: UN3257
Label Codes: 9
ERG Code: Not applicable for air transport



SECTION 15 REGULATORY INFORMATION

15.1 US Federal Regulations

Clarified Oils (Petroleum), catalytic cracked (64741-62-4)	
SARA Section 311/312 Hazard Classes	Health hazard – Carcinogenicity Health hazard – Reproductive toxicity Health hazard – Respiratory or skin sensitization Health hazard – Germ cell mutagenicity

Clarified Oils (Petroleum), catalytic cracked (64741-62-4)

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ (Naphthalene)	100 lbs
CERCLA RQ (Hydrogen Sulfide)	100 lbs

15.2 U.S. State Regulations

Decant Oil Distillation Residue (64741-62-4)
U.S. – Massachusetts – Right to Know List
U.S. – New Jersey – Right to Know List
U.S. – Pennsylvania – Right to Know List

California Proposition 65



WARNING: This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Clarified Oils (Petroleum), catalytic cracked (64741-64-2)	X			

SECTION 16: OTHER INFORMATION

Date of Preparation: 09/12/2025

Other Information: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Asp.1	May be fatal if swallowed and enters airways
Acute Tox. 4 (Inhale)	Harmful if inhaled
Muta. 2	Suspected of causing genetic defects
Carc. 1A	May cause cancer
Repr. 1B	May damage fertility or the unborn child
STOT RE 2	May cause damage to organs through prolonged or repeated exposure
Aquatic Acute 1	Very toxic to aquatic life

PETROLEUM PAVEMENT SEALER BASE

Safety Data Sheet

According to Fedral Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Chronic 1	Very toxic to aquatic life with long lasting effects
H304	May be fatal if swallowed and enters airways
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.